



WOOD

Seasons
Atelier Collection

Product
Datasheet
2015

WOOD

Seasons Atelier Collection



TECHNICAL INFORMATION	SEASONS
Thickness	14 mm
Width	162 mm
Length	2000-2520 mm
Wearlayer thickness (mm)	app. 3,5
Weight (kg/m ²)	app. 8,0
Taber Abraser/Lacquer's wear resistance* prEN 13696	
abrasion penetration Proteco Lacq.(revs)	>4000
abrasion penetration Proteco Nat.(revs)	>3500
abrasive wear (mg/100revs)	app. 3,5
<i>Data show results with new components according to 2006 update. Results not applicable for stained, brushed or hardwax oiled products.</i>	
Reduction of sound weighted index index "footfall" to the room below. NF EN ISO 140-8 / Acc to NF EN ISO 717-2, ΔL_w in dB with 2 mm Tarkofoam/flex II	17
Formaldehyde emission EN 13986	E1
Reaction to Fire EN 13501	D _{fl}
Thermal insulation value (RT m ² K/W)	
board only	0,101
with rag felt	0,121
with 2 mm Tarkofoam/flex II	0,141
Installation*	Floating / Glue down
Underfloor heating compatible**	Maximum floor surface temperature 27°C with self-regulating under-floor heat system.

* Contact your flooring supplier for further information.

** Not suitable for the woodspecies beech and maple.

SEASONS	Natura 2-lock
Plank, 14×2000-2520×162 mm. 2 side hand made maxibevel.	
Oak Spring brushed	•
Oak Summer brushed	•
Oak Autumn brushed	•
Oak Winter brushed	•

Seasons Proteco Natura



Wood floors, Brinell Hardness (BHN), EN1534

